

# SYNTHETIC MINOR OPERATING PERMIT

**PERMITTEE:** UCM MAGNESIA, INC.  
**FACILITY NAME:** UCM MAGNESIA, INC.  
**LOCATION:** CHEROKEE, ALABAMA

<b>PERMIT NUMBER</b>	<b>DESCRIPTION OF EQUIPMENT, ARTICLE OR DEVICE</b>
701-0015-X014	Furnace A (DC-01) Furnace B (DC-05) Electric Arc Furnace 1, 2, 3 (DC-10)

*In accordance with and subject to the provisions of the Alabama Air Pollution Control Act of 1971, as amended, Ala. Code §§22-28-1 to 22-28-23 (2006 Rplc. Vol. and 2007 Cum. Supp.) (the "AAPCA") and the Alabama Environmental Management Act, as amended, Ala. Code §§22-22A-1 to 22-22A-15 (2006 Rplc. Vol. and 2007 Cum. Supp.), and rules and regulations adopted there under, and subject further to the conditions set forth in this permit, the Permittee is hereby authorized to construct, install and use the equipment, device or other article described above.*

**ISSUANCE DATE:** DRAFT

**UCM MAGNESIA, INC.  
CHEROKEE, ALABAMA  
(PERMIT NO. 701-0015-X014)  
PROVISOS**

1. This permit is issued on the basis of Rules and Regulations existing on the date of issuance. In the event additional Rules and Regulations are adopted, it shall be the permit holder's responsibility to comply with such rules.
2. This permit is not transferable. Upon sale or legal transfer, the new owner or operator must apply for a permit within 30 days.
3. A new permit application must be made for new sources, replacements, alterations or design changes which may result in the issuance of, or an increase in the issuance of, air contaminants, or the use of which may eliminate or reduce or control the issuance of air contaminants.
4. Each point of emission will be provided with sampling ports, ladders, platforms, and other safety equipment to facilitate testing performed in accordance with procedures established by Part 60 of Title 40 of the Code of Federal Regulations, as the same may be amended or revised.
5. In case of shutdown of air pollution control equipment for scheduled maintenance for a period greater than one (1) hour, the intent to shut down shall be reported to the Air Division at least 24 hours prior to the planned shutdown, unless accompanied by the immediate shutdown of the emission source.
6. In the event there is a breakdown of equipment in such a manner as to cause increased emission of air contaminants for a period greater than one (1) hour, the person responsible for such equipment shall notify the Air Division within an additional 24 hours and provide a statement giving all pertinent facts, including the duration of the breakdown. The Air Division shall be notified when the breakdown has been corrected.
7. This process including all air pollution control devices and capture systems for which this permit is issued shall be maintained and operated at all times in a manner so as to minimize the emissions of air contaminants. Procedures for ensuring that the above equipment is properly operated and maintained so as to minimize the emission of air contaminants shall be established.
8. This permit expires and the application is cancelled if construction has not begun within 24 months of the date of issuance of the permit.
9. On completion of construction of the device for which this permit is issued, notification of the fact is to be given to the Chief of the Air Division. Authorization to operate the unit must be received from the Chief of the Air Division. Failure to notify the Chief of the Air Division of construction and/or operation without authorization could result in revocation of this permit.
10. Prior to a date to be specified by the Chief of the Air Division in the authorization to operate, emission tests are to be conducted by persons familiar with and using the EPA Sampling Train and Test Procedure as described in the Code of Federal Regulations, Title 40, Part 60, for the following pollutants. Written tests results are to be reported to the Air Division within 15 working days of completion of testing.

Particulates	(X)	Carbon Monoxide	( )
Sulfur Dioxide	( )	Nitrogen Oxides	( )

Volatile Organic Compounds ( )

Visible Emissions ( )

11. Submittal of other reports regarding monitoring records, fuel analyses, operating rates, and equipment malfunctions may be required as authorized in the Department's air pollution control rules and regulations. The Department may require stack emission testing at any time.
12. Additions and revisions to the conditions of this Permit will be made, if necessary, to ensure that the Department's air pollution control rules and regulations are not violated.
13. Nothing in this permit or conditions thereto shall negate any authority granted to the Air Division pursuant to the Alabama Environmental Management Act or regulations issued thereunder.
14. This permit is issued with the condition that, should obnoxious odors arising from the plant operations be verified by Air Division inspectors, measures to abate the odorous emissions shall be taken upon a determination by the Alabama Department of Environmental Management that these measures are technically and economically feasible.
15. The Air Division must be notified in writing at least 10 working days in advance of all emission tests to be conducted and submitted as proof of compliance with the Department's air pollution control rules and regulations.

To avoid problems concerning testing methods and procedures, the following shall be included with the notification letter:

- (1) The date the test crew is expected to arrive, the date and time anticipated of the start of the first run, how many and which sources are to be tested, and the names of the persons and/or testing company that will conduct the tests.
- (2) A complete description of each sampling train to be used, including type of media used in determining gas stream components, type of probe lining, type of filter media, and probe cleaning method and solvent to be used (if test procedure requires probe cleaning).
- (3) A description of the process(es) to be tested, including the feed rate, any operating parameter used to control or influence the operations, and the rated capacity.
- (4) A sketch or sketches showing sampling point locations and their relative positions to the nearest upstream and downstream gas flow disturbances.

A pretest meeting may be held at the request of the source owner or the Department. The necessity for such a meeting and the required attendees will be determined on a case-by-case basis.

All test reports must be submitted to the Air Division within 15 days of the actual completion of the test, unless an extension of time is specifically approved by the Air Division.

16. Precautions shall be taken to prevent fugitive dust emanating from plant roads, grounds, stockpiles, screens, dryers, hoppers, ductwork, etc.

**PERMIT NO. 701-0015-X014**

Plant or haul roads and grounds will be maintained in the following manner so that dust will not become airborne. A minimum of one, or a combination, of the following methods shall be utilized to minimize airborne dust from plant or haul roads and grounds:

- (a) by the application of water any time the surface of the road is sufficiently dry to allow the creation of dust emissions by the act of wind or vehicular traffic;
- (b) by reducing the speed of vehicular traffic to a point below that at which dust emissions are created;
- (c) by paving;
- (d) by the application of binders to the road surface at any time the road surface is found to allow the creation of dust emissions;

Should one, or a combination, of the above methods fail to adequately reduce airborne dust from plant or haul roads and grounds, alternative methods shall be employed, either exclusively or in combination with one or all of the above control techniques, so that dust will not become airborne. Alternative methods shall be approved by the Department prior to utilization.

- 17. The permittee shall not use as a defense in an enforcement action that maintaining compliance with conditions of this permit would have required halting or reducing the permitted activity.
- 18. The issuance of this permit does not convey any property rights of any sort, or any exclusive privilege.
- 19. Emissions of Particulate Matter from Arc Furnace A (DC-01) shall be limited to 0.013gr/cf (3.23 lb/hr).
- 20. Emissions of Particulate Matter from Arc Furnace B (DC-05) shall be limited to 0.013gr/cf (3.23 lb/hr).
- 21. Total Emissions of Particulate Matter from Electric Arc Furnaces 1, 2, and 3 (DC-10) shall be limited to 0.013 gr/cf (4.01 lb/hr).

# SYNTHETIC MINOR OPERATING PERMIT

**PERMITTEE:** UCM MAGNESIA, INC.  
**FACILITY NAME:** UCM MAGNESIA, INC.  
**LOCATION:** CHEROKEE, ALABAMA

<b>PERMIT NUMBER</b>	<b>DESCRIPTION OF EQUIPMENT, ARTICLE OR DEVICE</b>
701-0015-X015	MgO Calcining Kiln (DC-08)

*In accordance with and subject to the provisions of the Alabama Air Pollution Control Act of 1971, as amended, Ala. Code §§22-28-1 to 22-28-23 (2006 Rplc. Vol. and 2007 Cum. Supp.) (the "AAPCA") and the Alabama Environmental Management Act, as amended, Ala. Code §§22-22A-1 to 22-22A-15 (2006 Rplc. Vol. and 2007 Cum. Supp.), and rules and regulations adopted there under, and subject further to the conditions set forth in this permit, the Permittee is hereby authorized to construct, install and use the equipment, device or other article described above.*

**ISSUANCE DATE:** DRAFT

**UCM MAGNESIA, INC.  
CHEROKEE, ALABAMA  
(PERMIT NO. 701-0015-X015)  
PROVISOS**

1. This permit is issued on the basis of Rules and Regulations existing on the date of issuance. In the event additional Rules and Regulations are adopted, it shall be the permit holder's responsibility to comply with such rules.
2. This permit is not transferable. Upon sale or legal transfer, the new owner or operator must apply for a permit within 30 days.
3. A new permit application must be made for new sources, replacements, alterations or design changes which may result in the issuance of, or an increase in the issuance of, air contaminants, or the use of which may eliminate or reduce or control the issuance of air contaminants.
4. Each point of emission will be provided with sampling ports, ladders, platforms, and other safety equipment to facilitate testing performed in accordance with procedures established by Part 60 of Title 40 of the Code of Federal Regulations, as the same may be amended or revised.
5. In case of shutdown of air pollution control equipment for scheduled maintenance for a period greater than one (1) hour, the intent to shut down shall be reported to the Air Division at least 24 hours prior to the planned shutdown, unless accompanied by the immediate shutdown of the emission source.
6. In the event there is a breakdown of equipment in such a manner as to cause increased emission of air contaminants for a period greater than one (1) hour, the person responsible for such equipment shall notify the Air Division within an additional 24 hours and provide a statement giving all pertinent facts, including the duration of the breakdown. The Air Division shall be notified when the breakdown has been corrected.
7. This process including all air pollution control devices and capture systems for which this permit is issued shall be maintained and operated at all times in a manner so as to minimize the emissions of air contaminants. Procedures for ensuring that the above equipment is properly operated and maintained so as to minimize the emission of air contaminants shall be established.
8. This permit expires and the application is cancelled if construction has not begun within 24 months of the date of issuance of the permit.
9. On completion of construction of the device for which this permit is issued, notification of the fact is to be given to the Chief of the Air Division. Authorization to operate the unit must be received from the Chief of the Air Division. Failure to notify the Chief of the Air Division of construction and/or operation without authorization could result in revocation of this permit.
10. Prior to a date to be specified by the Chief of the Air Division in the authorization to operate, emission tests are to be conducted by persons familiar with and using the EPA Sampling Train and Test Procedure as described in the Code of Federal Regulations, Title 40, Part 60, for the following pollutants. Written tests results are to be reported to the Air Division within 15 working days of completion of testing.

Particulates	(X)	Carbon Monoxide	( )
Sulfur Dioxide	( )	Nitrogen Oxides	( )

Volatile Organic Compounds ( )

Visible Emissions ( )

11. Submittal of other reports regarding monitoring records, fuel analyses, operating rates, and equipment malfunctions may be required as authorized in the Department's air pollution control rules and regulations. The Department may require stack emission testing at any time.
12. Additions and revisions to the conditions of this Permit will be made, if necessary, to ensure that the Department's air pollution control rules and regulations are not violated.
13. Nothing in this permit or conditions thereto shall negate any authority granted to the Air Division pursuant to the Alabama Environmental Management Act or regulations issued thereunder.
14. This permit is issued with the condition that, should obnoxious odors arising from the plant operations be verified by Air Division inspectors, measures to abate the odorous emissions shall be taken upon a determination by the Alabama Department of Environmental Management that these measures are technically and economically feasible.
15. The Air Division must be notified in writing at least 10 working days in advance of all emission tests to be conducted and submitted as proof of compliance with the Department's air pollution control rules and regulations.

To avoid problems concerning testing methods and procedures, the following shall be included with the notification letter:

- (1) The date the test crew is expected to arrive, the date and time anticipated of the start of the first run, how many and which sources are to be tested, and the names of the persons and/or testing company that will conduct the tests.
- (2) A complete description of each sampling train to be used, including type of media used in determining gas stream components, type of probe lining, type of filter media, and probe cleaning method and solvent to be used (if test procedure requires probe cleaning).
- (3) A description of the process(es) to be tested, including the feed rate, any operating parameter used to control or influence the operations, and the rated capacity.
- (4) A sketch or sketches showing sampling point locations and their relative positions to the nearest upstream and downstream gas flow disturbances.

A pretest meeting may be held at the request of the source owner or the Department. The necessity for such a meeting and the required attendees will be determined on a case-by-case basis.

All test reports must be submitted to the Air Division within 15 days of the actual completion of the test, unless an extension of time is specifically approved by the Air Division.

16. Precautions shall be taken to prevent fugitive dust emanating from plant roads, grounds, stockpiles, screens, dryers, hoppers, ductwork, etc.

Plant or haul roads and grounds will be maintained in the following manner so that dust will not become airborne. A minimum of one, or a combination, of the following methods shall be utilized to minimize airborne dust from plant or haul roads and grounds:

- (a) by the application of water any time the surface of the road is sufficiently dry to allow the creation of dust emissions by the act of wind or vehicular traffic;
- (b) by reducing the speed of vehicular traffic to a point below that at which dust emissions are created;
- (c) by paving;
- (d) by the application of binders to the road surface at any time the road surface is found to allow the creation of dust emissions;

Should one, or a combination, of the above methods fail to adequately reduce airborne dust from plant or haul roads and grounds, alternative methods shall be employed, either exclusively or in combination with one or all of the above control techniques, so that dust will not become airborne. Alternative methods shall be approved by the Department prior to utilization.

- 17. The permittee shall not use as a defense in an enforcement action that maintaining compliance with conditions of this permit would have required halting or reducing the permitted activity.
- 18. The issuance of this permit does not convey any property rights of any sort, or any exclusive privilege.
- 19. Emissions of Particulate Matter from the Calcining Kiln (DC-08) shall be limited to 0.013 gr/cf (1.45 lb/hr).



# SYNTHETIC MINOR OPERATING PERMIT

**PERMITTEE:** UCM MAGNESIA, INC.  
**FACILITY NAME:** UCM MAGNESIA, INC.  
**LOCATION:** CHEROKEE, ALABAMA

PERMIT NUMBER	DESCRIPTION OF EQUIPMENT, ARTICLE OR DEVICE
701-0015-X016	MgO Classifying System (DC-02) Vibra Mill System (DC-09) MZ-80 Classifying System (DC-11)

*In accordance with and subject to the provisions of the Alabama Air Pollution Control Act of 1971, as amended, Ala. Code §§22-28-1 to 22-28-23 (2006 Rplc. Vol. and 2007 Cum. Supp.) (the "AAPCA") and the Alabama Environmental Management Act, as amended, Ala. Code §§22-22A-1 to 22-22A-15 (2006 Rplc. Vol. and 2007 Cum. Supp.), and rules and regulations adopted there under, and subject further to the conditions set forth in this permit, the Permittee is hereby authorized to construct, install and use the equipment, device or other article described above.*

**ISSUANCE DATE:** DRAFT

**UCM MAGNESIA, INC.**  
**CHEROKEE, ALABAMA**  
**(PERMIT NO. 701-0015-X016)**  
**PROVISOS**

1. This permit is issued on the basis of Rules and Regulations existing on the date of issuance. In the event additional Rules and Regulations are adopted, it shall be the permit holder's responsibility to comply with such rules.
2. This permit is not transferable. Upon sale or legal transfer, the new owner or operator must apply for a permit within 30 days.
3. A new permit application must be made for new sources, replacements, alterations or design changes which may result in the issuance of, or an increase in the issuance of, air contaminants, or the use of which may eliminate or reduce or control the issuance of air contaminants.
4. Each point of emission will be provided with sampling ports, ladders, platforms, and other safety equipment to facilitate testing performed in accordance with procedures established by Part 60 of Title 40 of the Code of Federal Regulations, as the same may be amended or revised.
5. In case of shutdown of air pollution control equipment for scheduled maintenance for a period greater than one (1) hour, the intent to shut down shall be reported to the Air Division at least 24 hours prior to the planned shutdown, unless accompanied by the immediate shutdown of the emission source.
6. In the event there is a breakdown of equipment in such a manner as to cause increased emission of air contaminants for a period greater than one (1) hour, the person responsible for such equipment shall notify the Air Division within an additional 24 hours and provide a statement giving all pertinent facts, including the duration of the breakdown. The Air Division shall be notified when the breakdown has been corrected.
7. This process including all air pollution control devices and capture systems for which this permit is issued shall be maintained and operated at all times in a manner so as to minimize the emissions of air contaminants. Procedures for ensuring that the above equipment is properly operated and maintained so as to minimize the emission of air contaminants shall be established.
8. This permit expires and the application is cancelled if construction has not begun within 24 months of the date of issuance of the permit.
9. On completion of construction of the device for which this permit is issued, notification of the fact is to be given to the Chief of the Air Division. Authorization to operate the unit must be received from the Chief of the Air Division. Failure to notify the Chief of the Air Division of construction and/or operation without authorization could result in revocation of this permit.
10. Prior to a date to be specified by the Chief of the Air Division in the authorization to operate, emission tests are to be conducted by persons familiar with and using the EPA Sampling Train and Test Procedure as described in the Code of Federal Regulations, Title 40, Part 60, for the following pollutants. Written tests results are to be reported to the Air Division within 15 working days of completion of testing.

Particulates	(X)	Carbon Monoxide	( )
Sulfur Dioxide	( )	Nitrogen Oxides	( )

Volatile Organic Compounds ( )

Visible Emissions ( )

11. Submittal of other reports regarding monitoring records, fuel analyses, operating rates, and equipment malfunctions may be required as authorized in the Department's air pollution control rules and regulations. The Department may require stack emission testing at any time.
12. Additions and revisions to the conditions of this Permit will be made, if necessary, to ensure that the Department's air pollution control rules and regulations are not violated.
13. Nothing in this permit or conditions thereto shall negate any authority granted to the Air Division pursuant to the Alabama Environmental Management Act or regulations issued thereunder.
14. This permit is issued with the condition that, should obnoxious odors arising from the plant operations be verified by Air Division inspectors, measures to abate the odorous emissions shall be taken upon as determined by the Alabama Department of Environmental Management that these measures are technically and economically feasible.
15. The Air Division must be notified in writing at least 10 working days in advance of all emission tests to be conducted and submitted as proof of compliance with the Department's air pollution control rules and regulations.

To avoid problems concerning testing methods and procedures, the following shall be included with the notification letter:

- (1) The date the test crew is expected to arrive, the date and time anticipated of the start of the first run, how many and which sources are to be tested, and the names of the persons and/or testing company that will conduct the tests.
- (2) A complete description of each sampling train to be used, including type of media used in determining gas stream components, type of probe lining, type of filter media, and probe cleaning method and solvent to be used (if test procedure requires probe cleaning).
- (3) A description of the process(es) to be tested, including the feed rate, any operating parameter used to control or influence the operations, and the rated capacity.
- (4) A sketch or sketches showing sampling point locations and their relative positions to the nearest upstream and downstream gas flow disturbances.

A pretest meeting may be held at the request of the source owner or the Department. The necessity for such a meeting and the required attendees will be determined on a case-by-case basis.

All test reports must be submitted to the Air Division within 15 days of the actual completion of the test, unless an extension of time is specifically approved by the Air Division.

16. Precautions shall be taken to prevent fugitive dust emanating from plant roads, grounds, stockpiles, screens, dryers, hoppers, ductwork, etc.

Plant or haul roads and grounds will be maintained in the following manner so that dust will not become airborne. A minimum of one, or a combination, of the following methods shall be utilized to minimize airborne dust from plant or haul roads and grounds:

- (a) by the application of water any time the surface of the road is sufficiently dry to allow the creation of dust emissions by the act of wind or vehicular traffic;
- (b) by reducing the speed of vehicular traffic to a point below that at which dust emissions are created;
- (c) by paving;
- (d) by the application of binders to the road surface at any time the road surface is found to allow the creation of dust emissions;

Should one, or a combination, of the above methods fail to adequately reduce airborne dust from plant or haul roads and grounds, alternative methods shall be employed, either exclusively or in combination with one or all of the above control techniques, so that dust will not become airborne. Alternative methods shall be approved by the Department prior to utilization.

- 17. The permittee shall not use as a defense in an enforcement action that maintaining compliance with conditions of this permit would have required halting or reducing the permitted activity.
- 18. The issuance of this permit does not convey any property rights of any sort, or any exclusive privilege.
- 19. Emissions of Particulate Matter from the MgO Classifying System (DC-02) shall be limited to 0.013 gr/cf (1.56 lb/hr).
- 20. Emissions of Particulate Matter from the Vibra Mill System (DC-09) shall be limited to 0.013 gr/cf (0.17 lb/hr)
- 21. Emissions of Particulate Matter from the MZ-80 Classifying System (DC-11) shall be limited to 0.013 gr/cf (0.39 lb/hr).

# SYNTHETIC MINOR OPERATING PERMIT

**PERMITTEE:** UCM MAGNESIA, INC.  
**FACILITY NAME:** UCM MAGNESIA, INC.  
**LOCATION:** CHEROKEE, ALABAMA

PERMIT NUMBER	DESCRIPTION OF EQUIPMENT, ARTICLE OR DEVICE
701-0015-X017	MgO Crusher/Grinder (DC-04) Electrical MgO Crusher/Grinder (DC-06) Friction MgO Crusher/Grinder (DC-07) ReClaim (DC-03) ZY Room (DC-12)

*In accordance with and subject to the provisions of the Alabama Air Pollution Control Act of 1971, as amended, Ala. Code §§22-28-1 to 22-28-23 (2006 Rplc. Vol. and 2007 Cum. Supp.) (the "AAPCA") and the Alabama Environmental Management Act, as amended, Ala. Code §§22-22A-1 to 22-22A-15 (2006 Rplc. Vol. and 2007 Cum. Supp.), and rules and regulations adopted there under, and subject further to the conditions set forth in this permit, the Permittee is hereby authorized to construct, install and use the equipment, device or other article described above.*

**ISSUANCE DATE:** DRAFT

**UCM MAGNESIA, INC.  
CHEROKEE, ALABAMA  
(PERMIT NO. 701-0015-X017)  
PROVISOS**

1. This permit is issued on the basis of Rules and Regulations existing on the date of issuance. In the event additional Rules and Regulations are adopted, it shall be the permit holder's responsibility to comply with such rules.
2. This permit is not transferable. Upon sale or legal transfer, the new owner or operator must apply for a permit within 30 days.
3. A new permit application must be made for new sources, replacements, alterations or design changes which may result in the issuance of, or an increase in the issuance of, air contaminants, or the use of which may eliminate or reduce or control the issuance of air contaminants.
4. Each point of emission will be provided with sampling ports, ladders, platforms, and other safety equipment to facilitate testing performed in accordance with procedures established by Part 60 of Title 40 of the Code of Federal Regulations, as the same may be amended or revised.
5. In case of shutdown of air pollution control equipment for scheduled maintenance for a period greater than one (1) hour, the intent to shut down shall be reported to the Air Division at least 24 hours prior to the planned shutdown, unless accompanied by the immediate shutdown of the emission source.
6. In the event there is a breakdown of equipment in such a manner as to cause increased emission of air contaminants for a period greater than one (1) hour, the person responsible for such equipment shall notify the Air Division within an additional 24 hours and provide a statement giving all pertinent facts, including the duration of the breakdown. The Air Division shall be notified when the breakdown has been corrected.
7. This process including all air pollution control devices and capture systems for which this permit is issued shall be maintained and operated at all times in a manner so as to minimize the emissions of air contaminants. Procedures for ensuring that the above equipment is properly operated and maintained so as to minimize the emission of air contaminants shall be established.
8. This permit expires and the application is cancelled if construction has not begun within 24 months of the date of issuance of the permit.
9. On completion of construction of the device for which this permit is issued, notification of the fact is to be given to the Chief of the Air Division. Authorization to operate the unit must be received from the Chief of the Air Division. Failure to notify the Chief of the Air Division of construction and/or operation without authorization could result in revocation of this permit.
10. Prior to a date to be specified by the Chief of the Air Division in the authorization to operate, emission tests are to be conducted by persons familiar with and using the EPA Sampling Train and Test Procedure as described in the Code of Federal Regulations, Title 40, Part 60, for the following pollutants. Written tests results are to be reported to the Air Division within 15 working days of completion of testing.

Particulates	(X)	Carbon Monoxide	( )
Sulfur Dioxide	( )	Nitrogen Oxides	( )

Volatile Organic Compounds ( )

Visible Emissions ( )

11. Submittal of other reports regarding monitoring records, fuel analyses, operating rates, and equipment malfunctions may be required as authorized in the Department's air pollution control rules and regulations. The Department may require stack emission testing at any time.
12. Additions and revisions to the conditions of this Permit will be made, if necessary, to ensure that the Department's air pollution control rules and regulations are not violated.
13. Nothing in this permit or conditions thereto shall negate any authority granted to the Air Division pursuant to the Alabama Environmental Management Act or regulations issued thereunder.
14. This permit is issued with the condition that, should obnoxious odors arising from the plant operations be verified by Air Division inspectors, measures to abate the odorous emissions shall be taken upon as determination by the Alabama Department of Environmental Management that these measures are technically and economically feasible.
15. The Air Division must be notified in writing at least 10 working days in advance of all emission tests to be conducted and submitted as proof of compliance with the Department's air pollution control rules and regulations.

To avoid problems concerning testing methods and procedures, the following shall be included with the notification letter:

- (1) The date the test crew is expected to arrive, the date and time anticipated of the start of the first run, how many and which sources are to be tested, and the names of the persons and/or testing company that will conduct the tests.
- (2) A complete description of each sampling train to be used, including type of media used in determining gas stream components, type of probe lining, type of filter media, and probe cleaning method and solvent to be used (if test procedure requires probe cleaning).
- (3) A description of the process(es) to be tested, including the feed rate, any operating parameter used to control or influence the operations, and the rated capacity.
- (4) A sketch or sketches showing sampling point locations and their relative positions to the nearest upstream and downstream gas flow disturbances.

A pretest meeting may be held at the request of the source owner or the Department. The necessity for such a meeting and the required attendees will be determined on a case-by-case basis.

All test reports must be submitted to the Air Division within 15 days of the actual completion of the test, unless an extension of time is specifically approved by the Air Division.

16. Precautions shall be taken to prevent fugitive dust emanating from plant roads, grounds, stockpiles, screens, dryers, hoppers, ductwork, etc.

Plant or haul roads and grounds will be maintained in the following manner so that dust will not become airborne. A minimum of one, or a combination, of the following methods shall be utilized to minimize airborne dust from plant or haul roads and grounds:

- (a) by the application of water any time the surface of the road is sufficiently dry to allow the creation of dust emissions by the act of wind or vehicular traffic;
- (b) by reducing the speed of vehicular traffic to a point below that at which dust emissions are created;
- (c) by paving;
- (d) by the application of binders to the road surface at any time the road surface is found to allow the creation of dust emissions;

Should one, or a combination, of the above methods fail to adequately reduce airborne dust from plant or haul roads and grounds, alternative methods shall be employed, either exclusively or in combination with one or all of the above control techniques, so that dust will not become airborne. Alternative methods shall be approved by the Department prior to utilization.

- 17. The permittee shall not use as a defense in an enforcement action that maintaining compliance with conditions of this permit would have required halting or reducing the permitted activity.
- 18. The issuance of this permit does not convey any property rights of any sort, or any exclusive privilege.
- 19. Emissions of Particulate Matter from the MgO Crusher/Grinder (DC-04) shall be limited to 0.013 gr/cf (1.56 lb/hr).
- 20. Emissions of Particulate Matter from the Electrical-Grade MgO Crusher/Grinder (DC-06) shall be limited to 0.013 gr/cf (1.28 lb/hr)
- 21. Emissions of Particulate Matter from the Friction-Grade MgO Crusher/Grinder (DC-07) shall be limited to 0.013 gr/cf (1.34 lb/hr).
- 22. Emissions of Particulate Matter from the Reclaim area (DC-03) shall be limited to 0.013 gr/cf (1.78 lb/hr).
- 23. Emissions of Particulate Matter from the ZY room (DC-12) shall be limited to 0.013 gr/cf (0.61 lb/hr).